

MOLD LIGHT BAR



Mold Light Bars provide illumination at the molding press to reduce eye strain and increase visibility for operators and repair technicians.

Light Bar Technical Information:

- Wire direct to 24V machine power or optional transformer
- Mounts to press platen magnetically to direct light on mold
- 12w 450mA

Light Bar Product Information:

- Six LED floodlights per unit. Rated for 50,000 hours
- Aluminum casting with tempered glass is water and shock resistant
- 45° and 90° swivel mounting brackets included
- IP67 Rated

Transformer Information:

- Plugs directly into 110v outlet
- Two screw wire connection

CATALOG NUMBER	DESCRIPTION	VOLTAGE	LENGTH	WIDTH
MLB2X16	Light Bar	24V	16"	2"
MLBTF	Transformer	110V 24V	—	—

SYNTHETIC MOLD GREASE



APPLICATION GUIDELINES

- Premium synthetic mold grease provides superior lubrication to sliding or moving components within molds and tooling.
- Engineered for food and medical molding environments
- Low migration
- Should only be applied in a thin layer by hand
- NSF H1 Registered
- Thermally stable to 570°F (300°C)

CATALOG NUMBER	DESCRIPTION
SYN-100	100g Tube
SYN-500	500g Tin