


# PIPE PLUGS

## NPT STANDARD




### APPLICATION GUIDELINES

- Standard Plugs are flush type, 7/8" taper per foot. Oversize Plugs available with 3/4" taper per foot.
- To order oversized Pipe Plugs, add a "-O" to the end of the catalog number. Ex. BR50-O.  
Note: Oversized not available in 2" Brass.

### M Brass, Alloy Steel, and Stainless Steel

PIPE THREAD NPT	BRASS CATALOG NUMBER	STEEL CATALOG NUMBER	STAINLESS CATALOG NUMBER	FLUSH HEIGHT	OVERSIZE HEIGHT
1/16	BR06	ST06	SS06	.25	.31
1/8	BR12	ST12	SS12	.25	.31
1/4	BR25	ST25	SS25	.40	.43
3/8	BR37	ST37	SS37	.40	.50
1/2	BR50	ST50	SS50	.53	.56
3/4	BR75	ST75	SS75	.53	.62
1	BR100	ST100	SS100	.65	.75
1-1/4	BR125	ST125	SS125	.65	.81
1-1/2	BR150	ST150	SS150	.65	.81
2	BR200	ST200	SS200	.65	.87


## NPT STANDARD-DEEP HEX



### M Brass

PIPE THREAD NPT	CATALOG NUMBER	HEIGHT
1/16	BRHD06	.289
1/8	BRHD12	.312
1/4	BRHD25	.445
3/8	BRHD37	.513
1/2	BRHD50	.625
3/4	BRHD75	.625

## BSPT STANDARD



### APPLICATION GUIDELINES

- Fits BSPT and BSPP threads.
- Identification ring present on bottom of plugs.

### M Brass, Alloy Steel, and Stainless Steel

PIPE THREAD	BRASS CATALOG NUMBER	STEEL CATALOG NUMBER	STAINLESS CATALOG NUMBER	HEIGHT (MM)
1/16-28 BSPT	BR06-BSP	ST06-BSP	SS06-BSP	7
1/8-28 BSPT	BR12-BSP	ST12-BSP	SS12-BSP	8
1/4-19 BSPT	BR25-BSP	ST25-BSP	SS25-BSP	10
3/8-19 BSPT	BR37-BSP	ST37-BSP	SS37-BSP	10
1/2-14 BSPT	BR50-BSP	ST50-BSP	SS50-BSP	10
3/4-14 BSPT	BR75-BSP	ST75-BSP	SS75-BSP	13
1-11 BSPT	BR100-BSP	-	-	14
1 1/4-11 BSPT	BR125-BSP	-	-	16